

Description

The polymeric calendered vinyl has excellent performance for injet printing.

Face film	Calendered PVC in Taiwan
Thickness	110 µm (4.4 mil) ±5%
Color and Finish	Gloss/Matt white cover

Release liner

Double-PE coated silicone paper with Japan tech and highly quality.

Weight	80 gsm ±5%
Thickness	120 µm ±5%
Color and Finish	White with Graphictac design

Adhesive

Clear , permanent , solvent-based adhesive.

Type	Acrylic
Apply Temp.	+10°C ~ +40°C
Adhesion (20 min)	1400 g/25mm
Adhesion (24 hour)	1650 g/25mm
Cohesion	24 hours↑ with 1 kg loading

Application

Decoration , moto & vehicle wrapping , advertising in outdoor graphics. Suitable on curved apply. Printable with solvent-based , UV and Latex.

Shelf life & Storage condition

Shelf life is 3 years in original packaging, at 25°C and 50% relative humidity.

Length and Width

Length	45 or 50 meter
Width	0.92m(36.2 inch)/1.27m(50inch)/1.55m (61 inch)



1000 Series **INKJET MEDIA**

SPECIFICATION

Code	Description	Width
1000-980	High glossy white	920/1270/1520
1000-981	Glossy white	920/1270/1550
1000-983	High opacity/glossy white	920/1270/1550
1000-983X	High opacity/glossy white with bubble free	920/1270/1550
1000-984	High opacity/matt white	920/1270/1550
1000-984X	High opacity/matt white with bubble free	920/1270/1550
1000-000	Tranparent	920/1270/1550
1000-509	Translucent glossy white	940/1270/1540
50-S01	Static cling/clear	1060
PP	Photo paper	920/1270/1524